



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224

Phone: 410-675-2100 or 800-543-3840

Revised: 05/24/2016

DAP® KWIK SEAL ULTRA™ Premium Siliconized Sealant – White & Biscuit

- Easy clean
- Repels water, stains & dirt
- Lifetime mold & mildew guarantee
- Sealant stays looking fresh & new
- 100% waterproof
- Crack & stain proof
- Safe for granite & marble
- Water ready in 4 hours
- Easy water clean up & low odor
- Interior

Packaging: 162 mL and 300 mL
Color: White, Biscuit
UPC Numbers: 7079874823, 7079874820, 7079874822

Company Identification:

Manufacturer: DAP Products Inc., 2400 Boston St., Suite 200, Baltimore, Maryland 21224
Usage Information: Call 1-888-DAP-TIPS or visit dap.com & click on “Ask the Expert”
Order Information: 800-668-9397 or 416-321-1522
Fax Number: 416-321-3325

Product Description:

DAP® KWIK SEAL ULTRA™ is a high performance siliconized kitchen and bath sealant that repels water, stains and dirt. It has a lifetime mold and mildew guarantee so the sealant stays looking fresh and new. **KWIK SEAL ULTRA™** is 100% waterproof and crack proof. It can be exposed to water in as little as 4 hours after application without washing out. It is safe for granite and marble, cleans up easily with water and is low in odor. Interior use.

Suggested Uses:

Ideal for sealing:

- *Tubs*
- *Sinks*
- *Backsplashes*
- *Showers*
- *Countertops*
- *Toilets*
- *Fixtures*
- *Loose Tile Repair*
- *Cracks and Joints*

Adheres To:

- Ceramic/Porcelain
- Glass
- Most Plastics
- Granite, Cultured Marble & Natural Stone
- Wood
- Metal
- Drywall
- Fiberglass
- Painted Surfaces

Performance Characteristics:

- Repels water, stains and dirt
- Lifetime mold & mildew guarantee
- Sealant stays looking fresh & new
- Water ready in 4 hours
- 100% waterproof
- Crack & stain proof
- Safe for granite & marble
- Easy water clean up and low odor
- Not paintable

For Best Results:

- Apply in temperatures above 4.5°C.
- Not for continuous underwater use, high temperature surfaces or surface defects.
- Joint size should not exceed 1cm wide by 1cm deep. For joints deeper than 31cm, use backer rod.
- Store product away from extreme heat or cold.

Surface Preparation & Application:

1. Surface must be clean, dry and free of all old sealant, dirt, dust, debris and grease. Rubbing alcohol is recommended for removing soap film and soil.
2. Remove cap (from tube). Cut nozzle at a 45° angle to desired bead size. If using the cartridge, puncture inner foil seal and load into caulk gun.
3. Fill gap with sealant, pushing sealant ahead of nozzle.
4. For a neat finish, smooth bead of sealant with a finishing tool.
5. Allow sealant to dry for at least 4 hours before exposing to water. Sealant reaches full performance in 24 hours.
6. Clean up excess uncured sealant with damp sponge before it skins over. Scrape or cut away excess cured sealant.
7. Regular cleaning of surrounding areas is suggested.
8. Reseal tube/cartridge for future use.

Typical Physical & Chemical Characteristics:

Tooling Time:	3-5 minutes
Tack Free Time:	8-10 minutes
Paintable:	No
Odor:	Very Mild
Consistency:	Smooth and Creamy
Vehicle:	Acrylic Polymer
Volatile:	Water
Flash Point:	None
Filler:	Titanium Oxide
Density:	1.04 kg/l
Solids:	58.2% by weight

Temperature Service Range: 0° F to 150°F

Temperature Application Range: 40°F to 100°F
Freeze Thaw Stability: Passes 5 Cycles
Applications: Interior
Shelf Life: 12 Months
Coverage: 162mL: 9.14m at a 0.5cm diameter bead or two average size bathtubs.
300mL: 17.07m or four average size bathtubs.
SDS No: 00079964605

Clean Up & Storage:

Remove excess uncured sealant with a damp cloth/sponge before it dries. After sealant has dried, excess sealant must be cut or scraped away. Store in a cool, dry place away from extreme heat or cold.

Safety:

This product does not pose any hazards to consumers under normal conditions of use. Do not get in eyes or on skin or clothing. Do not swallow. Keep out of reach of children. Use only in a well-ventilated area. Wear rubber gloves and safety glasses. In an emergency, call your poison control center at 1-800-222-1222. See product label and Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit dap.com.

Lifetime Mold & Mildew Guarantee:

DAP guarantees that the product when properly applied will remain free of mold and mildew during the lifetime of your home. If mold and/or mildew appear when used as directed, provide evidence of mold and mildew and sales receipt to DAP Canada for replacement product or sales price refund. DAP will not be liable for incidental or consequential damages.