



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 4/9/14

DAP[®] DRAFT ATTACK[®] Removable Weatherstrip Sealant

- Temporary, Removable Seal
- Seals Out Drafts
- Easily Peels Away
- Indoor/exterior use

Packaging: 300 mL
Color: Clear
UPC Number: 70798 70525 8

Company Identification:

Manufacturer: DAP Products Inc., 2400 Boston St., Baltimore, Maryland 21224
Usage Information: Call 1-888-DAP-TIPS or visit dap.com & click on "Ask the Expert"
Order Information: 800-327-3339
Fax Number: 410-534-2650
Also, visit the DAP website at www.dap.com.

Product Description:

DAP[®] DRAFT ATTACK[®] Removable Weatherstrip Sealant is formulated for use as a seasonal weatherstripping product. It provides a watertight, weatherproof and fast drying seal against air and moisture, keeping homes warmer in winter, cooler in summer, while also reducing energy bills. Use it to seal drafty windows, seasonally used doors, around air conditioners, vents or fans. Then peel away when no longer needed. Interior and exterior use.

Suggested Uses:

Ideal for sealing:

- *Window and door frames*
- *Patio doors*
- *Vents*
- *Air conditioners*
- *Fans*
- *Louvers*

Adheres to:

- *Glass*
- *Wood*
- *Ceramic/Porcelain*
- *Metal*
- *Aluminum*
- *Vinyl*

Surface Preparation & Application:

1. Remove any loose or foreign material.
2. Clean & dry surface. The surfaces must be free of creosote, oil, grease, wax, silicone, silicone-based product, asphalt or bitumen-based product, and any material soluble in solvents.
3. Trim nozzle to desired bead size. Cut the nozzle at a right angle (90°) slightly narrower than the width of the gap.
4. Puncture inner foil seal.
5. Load cartridge into caulking gun.
6. Fill gaps with sealant.
7. Do not shape or tool the bead.

DO NOT SEAL FIRE EXITS. ALLOW FRESH AIR ENTRY DURING APPLICATION AND DRYING.

FOR BEST RESULTS

- Apply in temperatures above 5°C.
- Store away from extreme heat or cold, below 27°C.
- Not for continuous underwater use.
- Do not use on freshly painted surfaces. Product may peel or damage wallpaper, fresh paint or loose uncured paint.
- Do not use on insulating panels or plastic materials which can be damaged by solvents
- New metal and solvent resistant oily surfaces must be washed with acetone and dried.
- For unusual substrates, perform a test for adhesion prior to use.
- For gaps wider than 6mm, backer rod should be used.
- The sealant should come into contact with each of the surfaces on a width of at least 3mm.
- If applied indoors, the area must be ventilated during application and drying time.
- Product left in place for more than 1 year may be difficult to remove.

Typical Physical & Chemical Characteristics:

Tooling Time:	Do not tool or shape bead
Tack Free Time:	10 Minutes
Service Expectancy:	Temporary – 12 months maximum
Paintability:	N/A
Odor:	Solvent
Consistency:	Smooth, gunnable paste
Polymer:	Synthetic rubber
Volatile:	Strong aliphatic and aromatic solvents
Flash Point:	39°F (4°C)
Filler:	N/A
Density:	Approximately 7lbs./gallon
Solids:	Approximately 52% by weight
VOC, less water and less exempts:	405 g/L (48%)
Temperature Service Range:	-25°C to 50°C
Temperature Application Range:	5°C to 38°C
Freeze/Thaw Stability:	Freeze thaw stable
Shelf Life:	12 months from date of manufacture when stored in unopened container below 30°C
Coverage: windows	15.2 linear meters at 5mm diameter bead size or 4 average size
SDS No.:	00017082605

Clean-Up & Storage:

While product is still wet use a solvent-moistened cloth. After the product has dried, excess material may be easily peeled away. Do not use solvent to clean hands. Reseal opened cartridge for future use. Store in a cool dry place, below 27°C, away from extreme cold or heat.

Safety:

Danger! Flammable, Irritant. FUMES MAY CATCH FIRE. MAY IRRITATE EYES AND SKIN. Do not smoke. Do not breathe fumes. Do not get in eyes, on skin or on clothing. Do not swallow. Use only in a well-ventilated area. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. Keep out of reach of children. Wear rubber gloves and safety goggles.

FIRST AID TREATMENT: Contains toluene. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. See product label and Safety Data Sheet (SDS) for additional information. For an SDS visit www.dap.com.

SATISFACTION GUARANTEED:

If product fails to perform within one year of purchase when used as directed, DAP Canada will either provide a replacement product or a sales price refund. Call 416-321-1522 with your sales receipt & product container available to arrange for warranty fulfillment. DAP Canada & its affiliates will not be liable for any incidental or consequential damages under any circumstances.

An  Company