



# Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224  
Phone: 410-675-2100 or 800-543-3840

Revised: 3/15/13

## DAP® FAST ‘N FINAL® Lightweight Spackling

- Patch & prime in one step
- Microsphere Technology – Provides ultra smooth surface for painting & hiding of repair
- Fast drying – paint in minutes
- Won’t shrink/crack
- No sanding
- Easy one strike application
- Interior/exterior
- Low VOC (Per CA Air Resource Board Test Method 310)
- Low odor

**Packaging:** 8 FL. OZ., 16 FL. OZ., 32 FL. OZ., 1 Gallon  
**Color:** Off White  
**UPC Numbers:** 70798 12140, 12148, 12145, 12146, 12141, 12147, 12142, 12143, 23030, 23050, 71354, 23090

### Company Identification:

**Manufacturer:** DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224  
**Usage Information:** DAP HELPLINE: 1-888-DAP-TIPS or [www.dap.com](http://www.dap.com) and click on “Ask the Expert”  
**Order Information:** 800-327-3339  
**Fax Number:** 410-558-1068  
Also, visit the DAP website at [dap.com](http://dap.com)

### Product Description:

**DAP® FAST ‘N FINAL® Lightweight Spackling** lets you patch and prime in one easy step, saving time and money. It dries fast with no need to sand or prime, letting you paint in minutes. It is easy to apply with one strike of the putty knife. The advanced, lightweight formula with Microsphere Technology provides an ultra smooth surface for exceptional hiding of the repair once painted. Won’t crack or shrink. Ideal for repairing holes, cracks and dents in drywall, plaster, wood and stucco. **DAP® FAST ‘N FINAL® Lightweight Spackling** has a low VOC content (per CA Air Resources Board Test Method 310) and is low in odor. Interior/exterior use.

### Suggested Uses:

Ideal for filling holes, cracks, crevices, dents or defects in:

- Drywall
- Wood
- Plaster
- Stucco

### **Surface Preparation & Application:**

- Surface must be clean, dry and free of foreign material.
- Mix gently before use.
- Using a clean putty knife, press spackling into hole or crack. Draw blade firmly across the surface to remove excess material in one strike.
- For a smoother finish, dip putty knife into water and lightly smooth spackling.
- One coat should be sufficient for small repairs
- May be painted within minutes with a latex paint. Please follow paint manufacturer's instructions for application.
- If sanding is desired, or if an oil-based paint is to be used, allow to dry thoroughly (approximately 24 hours).
- Clean tools immediately with water.

### ***For Best Results:***

- Do not apply when temperatures are below 40°F.
- Do not apply outside if rain is expected within 24 hours.
- Do not use on floors or as a caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur.
- **DO NOT USE AS A SKIM COAT.**
- For exterior application, first apply exterior-grade primer, then apply spackling and finish with coating of quality exterior-grade paint.
- Do not use for tuck pointing applications on brick.

### **Physical & Chemical Characteristics:**

Consistency:	Thick Paste
Vehicle:	Latex Polymer
Volatile:	Water
Filler:	Inert Filler
Odor:	Slight Acrylic
Weight/Gallon:	3.9 ± .3 pounds
Solids:	72.5 ± 1% by weight
Application Temperature:	40° F Minimum
Service Temperature:	-20°F to 150°F
Shelf Life:	12 Months
Freezing:	Freeze/Thaw Stable 5 Cycles at 0°F
Painting:	Takes either oil or latex-base paint
MSDS No.:	000 10410 001

### **Clean Up:**

Wash tools immediately after use with water. Dried material must be cut of scraped away. Be sure container lid is closed and tightly sealed. Store in a cool, dry place away from extreme heat or cold.

### **Safety:**

WARNING! IRRITANT. Contains: Sodium silicate glass, calcium carbonate and sodium Borate. May be harmful if inhaled. May cause eye, skin and respiratory irritation. Harmful if swallowed or absorbed through the skin. Do not breathe vapors or dust. Use only with adequate ventilation. Prevent build-up of dust and vapor by opening windows and doors or use other means to ensure fresh air entry during application, drying and sanding. Dry sanding of this product may generate dust. Inhalation of dust may cause lung damage or other adverse pulmonary and respiratory effects. When sanding, wear a NIOSH-approved dust mask. Follow dust mask manufacturer's directions for use. Keep exposure below OSHA permissible exposure limits. Avoid contact with eyes, skin and clothing. Wear gloves and safety glasses. Close container after use. Wash

thoroughly after handling. **WARNING:** This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. **FIRST AID: SKIN:** Wash thoroughly. **EYE:** Immediately flood with large quantities of water. **INHALATION:** Remove to fresh air. **INGESTION: DO NOT INDUCE VOMITING.** Get medical attention if complications arise from any exposure. For emergencies, call your poison control center at 1-800-222-1222. See product label and Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier, visit [dap.com](http://dap.com) or call 1-888-DAP-TIPS. **KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY**

**Satisfaction Guaranteed:**

If product fails to perform when used as directed, return used container and sales receipt to DAP Products Inc., Technical Customer Service, 2400 Boston Street, Suite 200, Baltimore, MD 21224 for product replacement or sales price refund. DAP will not be liable for incidental or consequential damages.