

# Safety Data Sheet

24 Hour Emergency Phone Numbers Medical/Poison Control: In U.S.: Call 1-800-222-1222

Outside U.S.: Call your local poison control center

Transportation/National Response Center:

1-800-535-5053 1-352-323-3500

NOTE: The National ResponseCenter emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this SDS are further described in Section 16.

## 1. Identification

This Safety Data Sheet is available in American Spanish upon request. Los Datos de Serguridad pueden obtenerse en Espanol si lo riquiere.

Product Name: Touch N Foam Professional Mine Sealant 2K Revision Date: 4/11/2022

Low GWP PU Foam Kit B Side

Product UPC Number: 075650212004 Supercedes Date: New SDS

Product Use/Class: Foam Sealant/Adhesive SDS No: 4762865

Manufacturer: DAP Global Inc. Imported by: DAP Canada

2400 Boston Street Suite 200 475 Finchdene Square Unit 5

Baltimore, MD 21224-4723 Scarborough, Ontario M1X 1B7 888-327-8477 (non - emergency matters) 888-327-8477 (non - emergency

matters)
SDS Coordinator: MSDS@dap.com

SDS Coordinator: Emergency Telephone: 1-800-535-5053, MSDS@dap.com

1-352-323-3500, 1-800-222-1222 Emergency Telephone:

1-800-535-5053, 1-352-323-3500

Preparer: Regulatory and Environmental Affairs

## 2. Hazards Identification

#### **GHS Classification**

Acute Tox. 4 Inhalation, Acute Tox. 4 Oral, Eye Irrit. 2, Gas under Pressure, Comp. Gas

### Symbol(s) of Product



# Signal Word

Warning

#### Possible Hazards

54% of the mixture consists of ingredients of unknown acute toxicity

#### **GHS HAZARD STATEMENTS**

Eye Irritation, category 2

Compressed Gas H280 Contains gas under pressure; may explode if heated.

Acute Toxicity, Oral, category 4 H302 Harmful if swallowed.

Acute Toxicity, Inhalation, category 4 H332 Harmful if inhaled.

#### **GHS LABEL PRECAUTIONARY STATEMENTS**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

H319

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

Causes serious eye irritation.

present and easy to do. Continue rinsing.

P330 Rinse mouth.

P337+P313 If eye irritation persists: Get medical advice/attention.
P410+P403 Protect from sunlight. Store in a well-ventilated place.

P501 Dispose of contents/container.

#### **GHS SDS PRECAUTIONARY STATEMENTS**

P270 Do no eat, drink or smoke when using this product.

# 3. Composition/Information on Ingredients

| Chemical Name  | CAS-No.     | Wt. % GHS Symbols    | <b>GHS Statements</b> |
|--|-------------|----------------------|-----------------------|
| 2-Butyne-1,4-diol, polymer with (chloromethyl) oxirane, brominated, dehydrochlorinated, methoxylated | 68441-62-3  | 10-30 GHS07          | H302-319              |
| Tris(2-chloro-1-methylethyl) phosphate   | 13674-84-5  | 10-30 GHS07          | H302-332              |
| Trans-1,3,3,3-Tetrafluoroprop-1-ene  | 29118-24-9  | 10-30 No Information | No Information        |
| 2-Butoxyethanol  | 111-76-2    | 1-5 GHS06-GHS07      | H302-311-315-319-330  |
| 1233zd HFO Propellant  | 102687-65-0 | 1-5 No Information   | No Information        |
| Glycerine  | 56-81-5     | 1-5 GHS06            | H331                  |
| Triethyl phosphate   | 78-40-0     | 1-5 GHS07            | H302-319              |

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

### 4. First-aid Measures

**FIRST AID - INHALATION:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

FIRST AID - SKIN CONTACT: Wash skin with soap and water for 15 minutes. Get medical aid if symptoms persist. Use a rag to remove excess foam from skin and remove contaminated clothing. Use of a solvent, such as acetone (nail polish remover) or mineral spirits, may help in removing uncured foam residue from clothing or other surfaces (avoid eye contact). Cured foam may be physically removed by persistent washing with soap and water. If irritation develops, use mild skin cream. If irritation persists, obtain medical attention.

FIRST AID - EYE CONTACT: In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

FIRST AID - INGESTION: If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

## 5. Fire-fighting Measures

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Closed containers may burst if exposed to extreme heat or fire. Containers may explode if exposed to extreme heat.

**SPECIAL FIREFIGHTING PROCEDURES:** Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Water Spray or Fog, Water

#### Accidental Release Measures

#### **ENVIRONMENTAL MEASURES:** No Information

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Use personal protective equipment as necessary. Read all product instructions before using. Personal protective equipment should include impervious gloves, protective eye wear, and suitable work clothes. Scrape up dried material and place into containers. Uncured product is very sticky, so carefully remove the bulk of the foam by scraping it up and then immediately remove residue with a rag and solvent such as polyurethane cleaner, mineral spirits, acetone (nail polish remover), paint thinner, etc. Once the product has cured, it can only be removed physically by scraping, buffing, etc. Dispose as plastic waste (foam plastic) in accordance with all applicable guidelines and regulations.

# 7. Handling and Storage

HANDLING: KEEP OUT OF REACH OF CHILDREN!DO NOT TAKE INTERNALLY. Make sure nozzle is directed away from yourself prior to discharge. Keep away from open flames, hot surfaces and sources of ignition. Wear appropriate personal protection. Avoid breathing vapor and contact with eyes, skin and clothing. Use only with adequate ventilation. Ensure fresh air entry during application and drying. Wash thoroughly after handling. Contains isocyanates. See information supplied by the manufacturer. Persons allergic to isocyanates, and particularly those suffering from asthma or other respiratory conditions, should not work with isocyanates.

**STORAGE:** Store away from sources of ignition and heat. Protect material from direct sunlight. Keep containers tightly closed in a dry, cool and well-ventilated place. Do not store at temperatures above 120 °F (49 °C). Store containers away from excessive heat and freezing. Store away from caustics and oxidizers.

## 8. Exposure Controls/Personal Protection

| Ingredients with Occupational Exposure Limits   |               |                |  |                  |
|---|---------------|----------------|--|------------------|
| Chemical Name   | ACGIH TLV-TWA | ACGIH-TLV STEL | OSHA PEL-TWA   | OSHA PEL-CEILING |
| 2-Butyne-1,4-diol, polymer with (chloromethyl)oxirane, brominated, dehydrochlorinated, methoxylated | N.E.          | N.E.           | N.E.   | N.E.             |
| Tris(2-chloro-1-methylethyl) phosphate  | N.E.          | N.E.           | N.E.   | N.E.             |
| Trans-1,3,3,3-Tetrafluoroprop-1-ene   | N.E.          | N.E.           | N.E.   | N.E.             |
| 2-Butoxyethanol   | 20 ppm TWA    | N.E.           | 50 ppm TWA, 240 mg/m3 TWA  | N.E.             |
| 1233zd HFO Propellant   | N.E.          | N.E.           | N.E.   | N.E.             |
| Glycerine   | N.E.          | N.E.           | 15 mg/m3 TWA<br>mist, total<br>particulate, 5 mg/m<br>TWA mist,<br>respirable fraction | N.E.<br>3        |
| Triethyl phosphate  | N.E.          | N.E.           | N.Ė.   | N.E.             |

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

### **Personal Protection**



**RESPIRATORY PROTECTION:** No personal respiratory protective equipment normally required. If concentrations exceed the exposure limits specified, use of a NIOSH-approved supplied air respirator is recommended. Where the protection factor is exceeded, use of a Self Contained Breathing Apparatus (SCBA) may be necessary. A respiratory

protection program that meets the OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.



SKIN PROTECTION: Wear nitrile, neoprene, or natural rubber gloves.



EYE PROTECTION: Goggles or safety glasses with side shields.



OTHER PROTECTIVE EQUIPMENT: Provide eyewash and solvent impervious apron if body contact may occur.



**HYGIENIC PRACTICES:** Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use.

Flammability, NFPA:

# 9. Physical and Chemical Properties

Appearance: Cream Physical State: Foam
Odor: Odor Threshold: Not Ex

Odor: Slight Solvent Odor Threshold: Not Established Density, g/cm3: 1.26 - 1.26pH: Not Applicable Not Established Viscosity (mPa.s): Not Aplicable Freeze Point, °C: Solubility in Water: Not Established Partition Coeff., n-octanol/water: Not Established Decomposition Temperature, °C: Not Established **Explosive Limits, %:** N.E. - N.E. Boiling Range, °C: Not Established N.A. - N.A. Auto-Ignition Temperature, °C Minimum Flash Point, °C: N.A. Vapor Pressure, mmHg: Not Established **Evaporation Rate:** Faster Than n-Butyl Acetate Flash Method: Not Applicable

Vapor Density: Heavier Than Air

Combustible Dust: Does not support combustion

(See "Other information" Section for abbreviation legend)

(If product is an aerosol, the flash point stated above is that of the propellant.)

## 10. Stability and Reactivity

**STABILITY:** Stable under recommended storage conditions.

**CONDITIONS TO AVOID:** Excessive heat and freezing.

**INCOMPATIBILITY:** Incompatible with strong bases and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal decomposition products, i.e., COx, NOx.

### 11. Toxicological Information

**EFFECT OF OVEREXPOSURE - INHALATION:** Vapors may be irritating to eyes, nose, throat, and lungs. Inhalation of high concentrations may cause headache, nausea, and dizziness.

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** May cause sensitization by skin contact. May cause localized irritation, reddening or swelling. Prolonged or repeated exposure may lead to sensitization and/or contact dermatitis. This product has strong adhesive-like characteristics and will adhere aggressively to skin and other surfaces. If accidental contact occurs, follow the appropriate first-aid procedure described in Section 4 of this SDS.

**EFFECT OF OVEREXPOSURE - EYE CONTACT:** Direct eye contact may cause irritation. Mist and vapors may cause eye irritation. Foam contact can cause physical damage due to adhesive character.

EFFECT OF OVEREXPOSURE - INGESTION: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

**CARCINOGENICITY:** No Information

**EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS:** Repeated or prolonged exposure may cause respiratory system damage. Repeated contact may cause allergic reactions in very susceptible persons.

Non-Flammable

PRIMARY ROUTE(S) OF ENTRY: Skin Contact, Inhalation, Eye Contact

#### **Acute Toxicity Values**

The acute effects of this product have not been tested. Data on individual components are tabulated below

| <u>CAS-No.</u> 68441-62-3 | Chemical Name 2-Butyne-1,4-diol, polymer with (chloromethyl) oxirane, brominated, dehydrochlorinated, methoxylated | Oral LD50<br>1337 mg/kg Rat | <u>Dermal LD50</u><br>N.I. | Vapor LC50<br>N.I. |
|---------------------------|--|-----------------------------|----------------------------|--------------------|
| 13674-84-5                | Tris(2-chloro-1-methylethyl) phosphate   | 1500 mg/kg Rat              | >5000 mg/kg Rabbit         | N.I.               |
| 29118-24-9                | Trans-1,3,3,3-Tetrafluoroprop-1-ene  | N.I.                        | N.I.                       | N.I.               |
| 111-76-2                  | 2-Butoxyethanol  | 470 mg/kg Rat               | 220 mg/kg Rabbit           | N.I.               |
| 102687-65-0               | 1233zd HFO Propellant  | N.I.                        | N.I.                       | N.I.               |
| 56-81-5                   | Glycerine  | 12600 mg/kg Rat             | >10000 mg/kg Rabbit        | N.I.               |
| 78-40-0                   | Triethyl phosphate   | 1100 - 1600 mg/kg Rat       | >20000 mg/kg Rabbit        | N.I.               |

N.I. = No Information

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** No Information

# 13. Disposal Information

**DISPOSAL INFORMATION:** Contents under pressure. Dispose of material in accordance with all federal, state and local regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste. Liquids cannot be disposed of in a landfill. Before disposing of containers, relieve container of any remaining product and pressure. Empty cylinders, once relieved of all pressure, can be disposed of as non-hazardous waste.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Use personal protective equipment as necessary. Read all product instructions before using. Personal protective equipment should include impervious gloves, protective eye wear, and suitable work clothes. Scrape up dried material and place into containers. Uncured product is very sticky, so carefully remove the bulk of the foam by scraping it up and then immediately remove residue with a rag and solvent such as polyurethane cleaner, mineral spirits, acetone (nail polish remover), paint thinner, etc. Once the product has cured, it can only be removed physically by scraping, buffing, etc. Dispose as plastic waste (foam plastic) in accordance with all applicable guidelines and regulations.

## 14. Transport Information

#### SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT UN/NA Number: UN3500

DOT Proper Shipping Name:
Chemical under pressure, n.o.s.
(Fluorinated hydrocarbon, Nitrogen)
DOT Hazard Class:

Chemical under pressure, n.o.s.
(Fluorinated hydrocarbon, Nitrogen)
2.2 Non-flamm compressed gas

Hazard SubClass: N.A. Packing Group: N.A.

# 15. Regulatory Information

#### **SARA SECTION 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

#### TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

# 16. Other Information

Revision Date: 4/11/2022 Supersedes Date: New MSDS

Reason for revision: HazCom2012/GHS Conversion

Datasheet produced by: Regulatory Department

**HMIS Ratings:** 

Health: Flammability: Reactivity: Personal Protection:

2\* 1 0 X

VOC Less Water Less Exempt Solvent, g/L: 0.0

VOC Material, g/L: 0

VOC as Defined by California Consumer Product Regulation, Wt/Wt%: 0.00

VOC Actual, Wt/Wt%: 0.0

### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

| H302 | Harmful if swallowed.          |
|------|--------------------------------|
|      |                                |
| H311 | Toxic in contact with skin.    |
| H315 | Causes skin irritation.        |
| H319 | Causes serious eye irritation. |
| H330 | Fatal if inhaled.              |
| H331 | Toxic if inhaled.              |
| H332 | Harmful if inhaled.            |

### Icons for GHS Pictograms shown in Section 3 describing each ingredient:



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.